

Digital Indicator

Model No. SCI - 502



► Features

- Peak, Hold, Data Protection(Key Lock), Auto Zero : Front Key or External Signal Terminal Operation
- Sampling Speed Control (Max 20Hz)
- Auto Calibration, Offset Function
- Filtering : 10Hz, 100Hz, 1kHz, W/B (User Selectable)

► Performance Specs

DISPLAY:

- Range: -19999 to 99999
- Decimal Point : Selectable Position
- 5-digit Segment FND
- Sampling rate 5KHz

SENSOR INPUT:

- DC 0 ~ ±10V, 0(4) ~ 20mA (User Selectable)
- Excitation Voltage : DC 24V, 15V(Optional)
- Accuracy : ±0.02% of reading
- Impedance : 100 Mohm`

POWER SUPPLY:

- AC supply voltage : 110, 220VAC, 50/60Hz, 15VA

ANALOG OUTPUT:

- NONE

DUAL LIMIT RELAYS :

- NONE

► Product Specification Chart

SCI - 502 - X X X

Communications

- 0 = None
 - 1 = RS232
 - 2 = RS485
 - 3 = BCD
 - 4 = Binary
- Option

Relays

- 0 = None

Operating power

- 0 = AC Power
- 1 = DC Power (Option)

► Dimensions (mm)

